

>>> RP-SR634

2+4-P Dual Wan Broadband Router



FEATURES

- Embedded Web-Based management interface
- Two WAN ports for load balance and redundant
- Friendly Configuration Wizard
- PPPoE protocol support
- DHCP server assigns dynamic or static IP addresses to client computers
- Static route lets user create routing table manually
- URL Blocking can limit access to certain Internet sites
- Outgoing / Incoming Policies for security or management consideration
- Port Mapping/Virtual Server allow WAN clients to access certain services provided by LAN clients
- Port Triggering open port forwarding dynamically
- System Log keep the track of services
- Wall-mountable

SPECIFICATIONS

Standard	IEEE802.3 for 10BASE-T IEEE802.3u for 100BASE-TX IEEE802.3x for Full-Duplex & Flow Control
Interface	WAN: 2 * 10/100Mbps RJ-45 port for Cable modem, or ADSL Internet connection LAN : 4 * 10/100Mbps RJ-45 switching ports
Connection Speed	. WAN: 10/100Mbps with auto MDI/MDI-X LAN : 10/100Mbps with auto MDI/MDI-X Duplex mode: Full and Half (LAN)
LED	. System: POWER, STATUS WAN: SPEED; LINK/ACT; FDX/COL LAN: SPEED; LINK/ACT; FDX/COL
Power	. DC12V1000mA
Dimension	210 * 148 * 35 mm
Certification	. FCC Class A, CE