

Fitting Series	PoE Adapter		
Photo			
Model	PSE15F	PSE 15F-48V-I	PSE30G-AT
Dimension	84.5mm*44mm*29.8mm	82.66*46.83 *40.26mm	132.3*60*33mm
Standard	IEEE802.3/ 802.3u	IEEE802.3/IEEE802.3u	IEEE802.3/802.3u/802.3ab/IEEE802.3af/at
Interface	1 FE Port (Data/PoE) 1 FE Port(Data)	1 FE Port (Data/PoE) 1 FE Port(Data)	1 GE Port (Data/PoE) 1 GE Port(Data)
Power Input	AC: 100-240V~50/60Hz	AC: 100-240V~50/60Hz	AC: 100-240V~50/60Hz
Power Output	DC 48V/0.3A(Max)	DC 48V/0.3A(Max)	DC: 51V/0.8A (Max)
Fitting Series	Optical Fiber Module		
Photo			
Model	G311SM	G511SM	G511MM
Description	Single-mode Optical Fiber Module	Single-mode Optical Fiber Module	Multi- mode Optical Fiber Module
Supported Media	IEEE 802.3z; CSMA/CD, TCP/IP	IEEE 802.3ae, CSMA/CD, TCP/IP	IEEE 802.3ae, CSMA/CD, TCP/IP
Connector Type	LC	LC	LC
Wavelength	1310nm	1310nm	850nm
Cable Distance	20km	10km	300m
Cable Distance	Working Temperature:0~40°C Storage Temperature:-40~70°C Working Humidity:10%~90%RH Storage Temperature:5%~90%RH	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing
Power Supply	3.3V	3.3V	3.3V
Automatic Recognition	SFP	SFP+	SFP+