



**Product:** [79002FS](#)

**SAFE-T-Line® Red 2 x 2.5 mm<sup>2</sup> LPCB**

**Product Description**

Safe-T-Line 2 x 2.5 mm<sup>2</sup> Fire resistant LPCB approved Multi-conductor, BS 6387 CWZ, EN 50200 PH120, Shielded, Silicone Rubber insulation, Low Smoke Zero Halogen Jacket

**Technical Specifications**

**Product Overview**

Suitable Applications:	Circuit integrity
------------------------	-------------------

**Physical Characteristics (Overall)**

**Conductor**

Stranding	Material	No. of Conductors
Solid	BC - Bare Copper	2

**Insulation**

Material
Silicone Rubber

**Color Chart**

Number	Color
Wire 1	Brown
Wire 2	Blue

**Outer Shield Material**

Material	Coverage [%]	Drainwire Material	Drainwire Diameter
Bi-Laminate (Alum+Poly)	100%	TC - Tinned Copper	0.8 mm

Table Notes:	Tape bonded to sheath
--------------	-----------------------

**Outer Jacket Material**

Material	Nominal Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)	9.2 mm

**Construction and Dimensions**

**Cabling**

Twists	
8.3 twist/m	
Overall Twisted Length:	120 mm

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR
7.41 Ohm/km

**Voltage**

<b>Voltage Rating [V]</b>
300/500 V

## Temperature Range

Installation Temp Range:	0°C To +70°C
Operating Temp Range:	-40°C To +90°C

## Mechanical Characteristics

Min Bend Radius During Operation:	6"D
-----------------------------------	-----

## Standards

CENELEC Compliance:	BS EN 60228
Other Compliance:	LPCB Certificate 1460a, BS6387 CWZ, EN50200:2015 PH120, EN50200:2015 Annex E30

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes

## Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2, IEC 60332-3-24 and IEC 60332-3-25
IEC 60754-1 (EN50267-1)- Halogen Amount:	IEC 60754-1
IEC 61034-2 (EN 61034-2) (VDE 0482-1034) - Smoke Density Min. Transmittance:	60%

## Part Number

### Variants

Item #	Color	Putup Type	Length	EAN
79002FS.00100	Red	Reel	100 m	8719605164025
79002FS.00400	Red	Reel	400 m	
79002FS.00500	Red	Reel	500 m	8719605164261
79002FS.01500	White	Reel	500 m	8719605164636

## Product Notes

Notes:	BS6387 CWZ: C- Fire @ 950°C - 180min, W - Fire & water @ 650°C - 15 + 15 min.,Z - Fire & mechanical shocks @ 950°C -15 min.
--------	---

## History

Update and Revision:	Revision Number: 0.48 Revision Date: 02-08-2021
----------------------	---

© 2021 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.